

# LOMO REGULAR

## STANDARDNO UKLJUČENO

- Wi-Fi sučelje
- Ionizator zraka
- Healthy filter
- Nevidljivi display
- Inteligentno automatsko pokretanje
- Samodijagnoza
- G10 tehnologija
- I-Feel funkcija
- Dizajn samosušenja protiv plijesni



MODEL	UČINAK (W)		ENER. KLASA SEER / SCOP	DIMENZIJE V / Š / D (mm)
	HLADNJE	GRIJANJE		
GWH09QB-K6DNA5E/I	2700 (450-3500)	2800 (450-4200)	6,8/4,0 (A++/A+)	275/790/200 540/776/320
GWH09QB-K6DNA1E/O				
GWH12QC-K6DNA5D/I	3500 (700-4000)	3670 (800-4500)	7,0/4,0 (A++/A+)	289/845/209 596/848/320
GWH12QC-K6DNA1D/O				
GWH18QD-K6DNA5D/I	5200 (1260-6600)	5300 (1120-6800)	7,0/4,0 (A++/A+)	300/970/224 700/965/396
GWH18QD-K6DNA1D/O				
GWH24QE-K6DNA5E/I	7000 (1930-8850)	7400 (1800-10630)	6,5/4,0 (A++/A+)	325/1078/246 700/963/396
GWH24QE-K6DNA1E/O				



-22°C ~ 24°C  
-15°C ~ 43°C



CJEVOVOD	UČINAK (kW)			
	2,7	3,5	5,2	7,0
Max. visinska razlika [m]	10	10	10	10
Max. duljina instalacije [m]	15	20	25	20
Promjer cijevi tekuće faze [mm]	6,35	6,35	6,35	6,35
Promjer cijevi plinovite faze [mm]	9,52	9,52	12,7	15,88

MODEL	UČINAK (W)		ENER. KLASA SEER / SCOP	DIMENZIJE V / Š / D (mm)
	HLADNJE	GRIJANJE		
GWH12YC-K6DNA1A/I	3500 (1000-3810)	3810 (1200-4400)	8,5/4,4 (A+++ / A+)	290/865/210 596/848/320
GWH12YC-K6DNA1A/O				
GWH18YD-K6DNA1A/I	5300 (1260-6600)	5570 (1120-6800)	7,6/4,1 (A++ / A+)	301/996/225 700/955/396
GWH18YD-K6DNA1A/O				
GWH24YE-K6DNA1A/I	7000 (1100-9050)	7200 (1710-10100)	7,0/4,0 (A++ / A+)	327/1101/249 700/955/396
GWH24YE-K6DNA1A/O				

# AMBER

## STANDARDNO UKLJUČENO

- Wi-Fi sučelje
- Led display
- Automatsko pokretanje
- Inteligentno predzagrijavanje
- Inteligentno odmrzavanje
- I-Feel
- Cold Plasma
- 7 brzina ventilatora

CJEVOVOD	UČINAK (kW)		
	3,5	5,3	7,0
Max. visinska razlika [m]	10	10	10
Max. duljina instalacije [m]	20	25	25
Promjer cijevi tekuće faze [mm]	6,35	6,35	6,35
Promjer cijevi plinovite faze [mm]	9,52	12,7	15,88



12k i 18k: -22°C ~ 24°C  
-15°C ~ 43°C  
24k: -15°C ~ 24°C  
-15°C ~ 43°C

