



PODSTROPNA JEDINICA

Snažna podstropna jedinica može se ugraditi uz pod te uz strop. Vanjska jedinica opremljena je grijačem kompresora i kadice kondenzata a pozlaćene lamele izmjenjivača jamstvo su dugotrajnosti

DALJINSKI UPRAVLJAČ

S uređajem se isporučuje bežični daljinski upravljač modernog dizajna s pozadinskim osvjetljenjem



HCO48/55YMV



HCO36YMV



HCO24YMV



HCO18YMV



HCO12YMV

**PODRUČJE
RADA**



OD **-15°C** (-15°C)
DO **+50°C**



OD **-20°C**
DO **+24°C**

**ENERGETSKA
UČINKOVITOST**

SEER
6,1

A++

SCOP
4,0

A+

Podaci se odnose na model učina 5,3 kW.
Podaci u zagradi odnose se na modele učina 10,5/14,0/16,0 kW



Unutarnja jedinica			HCF 18 VMV	HCF 24 VMV	HCF 36 VMV	HCF 48 VMV	HCF 55 VMV
Vanjska jedinica			HCO 18 VMV	HCO 24 VMV	HCO 36 YMV	HCO 48 YMV	HCO 55 YMV
Rashladni učin	kW	*	5,28	7,0	10,55	14,07	15,83
Raspon rashladnog učina (min.-max.)	kW	*	2,64 - 6,15	3,22 - 8,29	3,93 - 12,02	4,96 - 15,11	5,28 - 17,00
Potrošnja el. energije	kW	*	0,28 - 2,05	0,48 - 2,93	0,87 - 4,50	1,16 - 6,00	1,23 - 6,50
SEER / Energetska klasa			6,1 / A++	6,1 / A++	6,1 / A++	6,1 / A++	6,1 / A++
Učin grijanja	kW	☀	5,57	7,62	11,14	16,12	18,17
Raspon učina grijanja (min.-max.)	kW	☀	2,27 - 7,03	2,72 - 8,65	2,81 - 13,95	3,81 - 18,07	4,40 - 19,64
Potrošnja el. energije	kW	☀	0,33 - 2,18	0,50 - 2,85	0,73 - 4,89	1,03 - 6,2	1,02 - 6,55
SCOP / Energetska klasa			4,00 / A+	4,00 / A+	4,00 / A+	4,00 / A+	4,00 / A+
Unutarnja jedinica			HCF 18 VMV	HCF 24 VMV	HCF 36 VMV	HCF 48 VMV	HCF 55 VMV
Protok zraka	m ³ /h	*	902	1208	2160	2329	2454
Razina buke	dB(A)	*	37 / 45	41 / 50	42 / 51	46 / 54	42 / 54
Dimenzije (V×Š×D)	mm		235 x 1068 x 675	235 x 1068 x 675	235 x 1650 x 675	235 x 1650 x 675	235 x 1650 x 675
Težina	kg		26,6	26,8	39	41,2	41,4
Vanjska jedinica			HCO 18 VMV	HCO 24 VMV	HCO 36 YMV	HCO 48 YMV	HCO 55 YMV
Razina buke	dB(A)	*	55	62	65	66	66
Dimenzije (V×Š×D)	mm		554 x 800 x 333	702 x 845 x 363	810 x 946 x 410	1333 x 952 x 415	1333 x 952 x 415
Težina	kg		33,7	66,8	66,8	106,7	111,3
Tip kompresora			rotacijski klipni	rotacijski klipni	rotacijski klipni	rotacijski klipni	rotacijski klipni
Promjer cijevi - plin	mm (col)		12,7 (1/2")	15,88 (5/8")	15,88 (5/8")	15,88 (5/8")	15,88 (5/8")
Promjer cijevi - tekućina	mm (col)		6,35 (1/4")	9,52 (3/8")	9,52 (3/8")	9,52 (3/8")	9,52 (3/8")
Maksimalna duljina cijevi	m		30	50	65	65	65
Maksimalna visinska razlika	m		20	25	30	30	30
Napon priključka	V-Ph-Hz		230 - 1 - 50	230 - 1 - 50	400 - 3 - 50	400 - 3 - 50	400 - 3 - 50
Radna tvar/GWP			R32/675	R32/675	R32/675	R32/675	R32/675
Punjenje u kg/tona CO ₂ - EKV			1,15/0,78	1,50/1,01	2,40/1,62	2,80/1,89	2,95/1,99

☀ hlađenje ☀ grijanje

S uređajem se isporučuje bežični daljinski upravljač.